

86" Wi-Fi Interactive Flat Panel

50 simultaneous touch points LED ULTRA HD

Integrated touch | Infrared technology | Ambient light sensor 15Wx2+20Wx2 Integrated speakers | Bytello Share license included USB Type-C Full-Link 100W

HX8610

IFP 86" X SERIES WI-FI RDM READY+WALL MOUNT















Zero Gap Technology allows sharper images with better contrast and reduced glare.

Automatic brightness adjustment via ambient light sensor.



Infrared technology touch screen; usable even with gloves or any other solid object.

Anti-glare tempered glass with Mohs 7 4mm thickness.



Integrated 15Wx2 and 20Wx2 stereo speakers. Total power 30W + 40W



4x HDMI IN, 1x USB Type-C Full-Link 100W, 1x USB Type-C Full-Link 15W, 4x USB 3.0, 1x USB 2.0 OTG, 2x TOUCH OUT, 1x Display Port, 1x RS232, 2x LAN (RJ45 -Autoswitching)



CPU Octa Core A76×4+A55×4 8GB RAM. 128GB ROM **OPS Standard slot**

SI07B Wi-Fi and Bluetooth module included



Remote Display Management License included (1 year)*


Software Touch Display+ Bytello Share

Perpetual license


| | Code HX8610 | | | | |
|-----------|---------------------------|--|--|--|--|
| | Lighting | Direct type LED | | | |
| | Quality | Grade A | | | |
| | Display area | 189,5 × 106,6mm | | | |
| | Diagonal | 86" | | | |
| | Aspect ratio | 16:9 | | | |
| | Resolution | UltraHD 4K | | | |
| ₹ | Color depth | 1.07 billion (10 bits) | | | |
| DISPLAY | Brightness | 560 cd/m² - 600 cd/m² | | | |
| | Contrast | 6.000:1 | | | |
| | Viewing angle | 178° | | | |
| | Refresh rate | 60Hz | | | |
| | Response time | ≤lms | | | |
| | Sensors | Ambient light | | | |
| | Touch technology | Infrared matrix | | | |
| | Driver | HID | | | |
| | Simultaneous touch points | Up to 50 (Windows) | | | |
| ГОИСН | Input tools | Fingers (even with gloves) or any other passive object | | | |
| 5 | Object size | ≤1.6mm | | | |
| | Response time | ≤1.3ms | | | |
| | Accuracy | ±0.5 mm (touch area greater than 90%) | | | |
| | land the second section | | | | |
| | Input resolution | 32768(W)×32768(D) | | | |
| | Surface | 32768(W)×32768(D) Anti-reflective tempered glass 4mm Mohs level 7 | | | |
| АТА | · | | | | |
| тесн рата | Surface | Anti-reflective tempered glass 4mm Mohs level 7 | | | |

| INTERFACE | Input | 4x HDMI IN (2x front), 1x USB Type-C Full-Link 100W (front), 1x USB Type-C Full-Link 15W (rear), 4x USB 3.0 (2x front), 1x USB 2.0 OTG, 2x TOUCH OUT, 1x Display Port, 1x RS232, 2x LAN (RJ45 - Autoswitching) | | | |
|--------------------|--------------------------------------|--|---|--|--|
| | Output | 1x HDMI OUT, 1x USB Type-C OUT, 1x Audio OUT, 1x SPDIF | | | |
| | Connectivity | Ethernet LAN, Wi-Fi, Bluetooth, HotSpot | | | |
| | Speaker power | 2×15W+2×20W | | | |
| | OPS slot | Compatible | Compatible with OPS Standard 80 Pin | | |
| | System version | Android 13 | | | |
| ANDROID OS | Compatible applications | GSuite, Google Apps, Microsoft Office, Microsoft Teams, Cisco Webex, Zoom, Google Chrome, Mozilla Firefox, Skype | | | |
| | App installation | All apps compatible with the Android version of system (function can be deactivated) | | | |
| | CPU | Octa Core A76×4+A55×4 | | | |
| | GPU | Mali-G610 MP4 | | | |
| | RAM | 8 GB | | | |
| | SSD | 128 GB | | | |
| | Maximum consumption | 570W | | | |
| ENERGY | Standby consumption | ≤0.5W | | | |
| H | Ligfetime | ≥60.000 Hours | | | |
| | Operating time | 24/7 | | | |
| ORIES | Content of the package | 1x EU / UK Power Cord (3m), 1x HDMI (3m), 1x USB (5m), User Manual, 2x Passive Pens 1x Remote Control (batteries included), 1x SI07B (Wi-Fi Module), 1x wall mounting | | | |
| ACCESSORIES | Included software | Note (Android), Note ^{PLUS} (Windows) Capture (Windows), BytelloClass (Android) | | | |
| ∢ | Chimpa RDM included license | 1 year since enrollment* | | | |
| Certifications | | | Warranty | | |
| Ene | EnergyStar**, ROhs, CE, SGS***, EDLA | | 3 years on center | | |
| Admitted languages | | | Catalan, Czech, Danish, German, Estonian, English, Spanish, French, Croatian, Italian, Hungarian, Dutch, Norwegian, Polish, Portuguese, Romanian, Turkish, Swedish, Greek, Russian, Arabic, Chinese, Japanese, Lithuanian. | | |

| Environmental Conditions | ironmental Conditions | | | | | |
|--------------------------|-----------------------|---------------------|------------------|------------------|--|--|
| Operation temperature | Operation humidity | Storage temperature | Storage humidity | Altitude | | |
| 0°C~40°C | 10%~90%RH | -20°C~ 60°C | 10%~90%RH | less than 5000 m | | |









^{*}Warning: Chimpa RDM license is included in Interactive Flat Panel's price, but needs to be activated by the user. To manage the procedure, please contact education@ligra.it education@ligra.it ***Compliant with the European directive 2009/125/CE, known as ErP "Energy related Products" equivalent of American Energy Star
****Exclusive material treatment - Prevents the proliferation of common germs and bacteria













www.HELGI-europe.com

HELGI Europe education@helgi-europe.com business@helgi-europe.com

#191023HX8610_EN

| Dealer | | | |
|---------|--|--|--|
| D GGIOI | | | |
| | | | |
| | | | |
| | | | |
| | | | |